

IDEAL 2000 VINYL WINDOW

NFRC Testing

	SHGC	VT	NFRC 500	U-Factor
Clear Glass	0.53	0.56	43	0.44
Clear Glass w/argon	0.53	0.56	44	0.43
Low E	0.29	0.47	52	0.33
Low E w/argon	0.28	0.47	55	0.30

Test window size 50"x 63"

Test data provided by Quality Testing Inc., Everett, WA

Tests are NFRC 100, 200, 500

IDEAL 5000 VINYL WINDOW

NFRC Testing

	SHGC	VT	NFRC 500 CRV	U-Factor
Clear Glass	0.52	0.56	43	0.42
Clear Glass w/argon	0.52	0.56	45	0.41
Low E	0.28	0.47	53	0.31
Low E w/argon	0.28	0.47	56	0.28

Test window size 50"x 63"

Test data provided by Quality Testing Inc., Everett, WA

Tests are NFRC 100, 200, 500

IDEAL 2000 and IDEAL 5000 AAMA TEST RESULTS

Window Model	Window Type	Final Grade	Air Infiltration	Water Resistance	Structural Strength	Forced Entry	NFRC Certified
IDEAL 2000	O	F-C50	.01@1.57	12	75		YES
	X	DA-C30	.02@1.57	4.5	45	PASS	YES
	XO	DA-C30	.02@1.57	4.5	45	PASS	YES
	XOX	DA-C30	.02@1.57	4.5	45	PASS	YES
IDEAL 5000	O	F-C50	.01@1.57	12	75		YES
	X	DA-C35	.08@1.57	9	52.5	PASS	YES
	XO	DA-C35	.08@1.57	9	52.5	PASS	YES
	XOX	DA-C35	.08@1.57	9	52.5	PASS	YES

Test data provided by Quality Testing Inc., Everett, WA